


NOTES:	
Traffic sign	Diversion
Cone	Diversion
Work Area	WORKS ACCESS
Safety Zone	WORKS EXIT
Works access/works exit to be risk assessed on site for suitability of location	

### TRAFFIC MANAGEMENT NOTES

#### MULTI - PHASE TRAFFIC SIGNALS :

- NOTES
- All traffic signs shall comply with Chapter 8 of the Traffic Signs Manual
  - Maximum distance between any two temporary traffic signals to be 249m. Minimum distance between any two temporary traffic signals to be 30m.
  - Temporary traffic signals shall not occur within 150m of an existing level crossing. Pelican crossing or signalised junction without the consent of the Engineer. The Engineer shall consult with the authority responsible for any of these types of facility prior to traffic management being installed in adjacent areas.
  - Coning shall be installed at 45° to the edge of carriageway, as generally indicated.
  - Multi-phase portable traffic signals shall operate in vehicle actuated (VA) mode at all times unless otherwise directed by the Engineer.
  - Multi-phase portable traffic signals shall only be installed with the written permission of the local highway authority whose roads they are installed on.
  - Cable crossing protectors and P7010/P7013 signs shall be provided whenever control cables cross a section of carriageway open to traffic.
  - The signal control mechanism shall normally be placed in a location from which it is possible to view all approaches to the site.
  - Duplicate primary signal to be installed as instructed.
  - Lane width past the works to be 3.7m maximum, 3.25m desirable minimum, 3.0m absolute minimum.

SPEED OF ROAD:	
LONGWAYS:	15m
SIDEWAYS:	0.5m



A	35	A	10
B	35	B	10
C	35	C	10
D		D	

CLIENT:

SITE:  
Mulberry Cottage, Wexham Park Ln, Slough SL3 6LX

GRID REF: -----

TITLE: THREE WAY TEMPORARY TRAFFIC SIGNALS

SCALE AT 13: NTS	DATE:	DRAWN: JORDAN.C	CHECKED: JACK . B
DWG NO: TMSW6241	REV NO:	001	

- NOTES:
- All signs and cones to be in accordance with Chapter 8 new roads and street works a code of practice (Red book)
  - Works access and egress are indicative, exact locations to be agreed on site.
  - Safety zones are to be installed as required as shown by the SAFETY ZONE DIMENSIONS BELOW
  - All signs to be located so as not to obscure signs or objects and should be ballasted near to ground level using sand filled hessian bags or sign straps.
  - All sign positions are indicative only and must be accurately positioned on site with good visibility and be clear of and obstructions or vegetation at all times.
  - Drawing not to scale

**DETAIL A (A)**

Prescribed sign to Diagram 610 above and behind cones

Running lane(s)

Hard Shoulder

Verge

Notes:

- During darkness, a single warning light to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).
- 45° tapers have 1.5m spacing, no relaxations.
- On motorways and NSL AP duals with hard shoulders, 1m cones will be required for both standard and relaxation works for lead tapers and the facing wall of lane changes.

**DETAIL B (B)**

Single/Dual carriageway 40mph or less - 450mm traffic cones, spacing 1.5m. Single/Dual carriageway 50mph or more - 750mm traffic cones, spacing 1.5m. Dual carriageway national speed limit - 750mm traffic cones, spacing 1.5m, relaxation 3m.

Notes:

- During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).
- 45° tapers have 1.5m spacing, no relaxations.
- On motorways and NSL AP duals with hard shoulders, 1m cones will be required for both standard and relaxation works for lead tapers and the facing wall of lane changes.