

30

SAFETY ZONE DIMENSIONS

Permanent speed limit 30mph or less











Sideways safety zone 0.5m

Longways safety zone 0.5m

(Dimensions are minima)

Drawing Details
Drawing Number - JH1598
Drawn By - JH
Date Drawn - 29/11/2025
Surveyed By - JH
Date Surveyed - 29/11/2025
Checked By - PT
Phase Number - 1 of 1
Page Number - 1 of 1

Site Address Details
Farnham Road Phase 12 Slough SL1 3FW
Traffic Management Scheme
3 Way Lights 4 Pedestrian Crossings

Drawing Keys	
	Area of Works
	Safety Zones
	Temporary Traffic Signals
	750mm Road Signs
	900mm/1200mm Road Signs
	750mm/1m Road Cones
	No Parking/Waiting Cones
	Overhead Cable Cones
	Pedestrian Ramps
	Pedestrian Barriers

Pedestrian Timings		STAGING DIAGRAM			
	BLACKOUT	STAGE 1	STAGE 2	STAGE 3	STAGE 4
	<div>5</div>	<div><div></div><div></div></div>	<div><div></div><div></div></div>	<div><div></div><div></div></div>	<div><div></div><div></div></div>
	RED TIMINGS	RED TIMINGS			
	<div>2</div>	<div>20</div>	<div>20</div>	<div>20</div>	<div>10</div>
	GREEN TIMINGS	GREEN TIMINGS			
<div>7</div>	<div>40</div>	<div>40</div>	<div>40</div>	<div>35</div>	

Drawing Notes
1. Do not scale from this drawing, all dimensions to be verified on site.
2. It will be the responsibility of the contractor to ensure that all temporary traffic management shall be in accordance with the Traffic Signs Manual chapter 6 2009.
3. All signage placement will be subject to available safe working space and all signage will be secured / ballasted with straps or sandbags.
4. A minimum lateral safety zone of 0.5M will be maintained at all times.
5. A minimum running lane of 3.0m will be maintained for vehicles.
6. A safe segregated working area will be provided and maintained at all times.
7. Minimum size of temporary signage will be 750mm.