

SAFETY ZONE DIMENSIONS (S)
Permanent speed limit 30mph or less
Sideways safety zone 0.5m
Longways safety zone 0.5m
(Dimensions are minima)

Drawing Details

Drawing Number - JH1634

Drawn By -

Date Drawn - 02/12/2022


Surveyed By - J

Date Surveyed - 02/12/2024

Checked By - PT

Site Address Details

Drawing Keys

| | |
|---|---------------------------|
|  | Area of Works |
|  | Safety Zones |
|  | Temporary Traffic Signals |
|  | 750mm Road Signs |
|  | 900mm/1200mm Road Signs |
|  | 750mm/1m Road Cones |
|  | No Parking/Waiting Cones |
|  | Overhead Cable Cones |
|  | Pedestrian Ramps |
|  | Pedestrian Barriers |

Traffic Management Scheme

Road Narrows

STAGING DIAGRAM

STAGING DIAGRAM

| | | | | | |
|---------------------------|---|---|--|--|--|
| Pedestrian Timings | BLACKOUT  | STAGE 1 STAGE 2 STAGE 3 STAGE 4 | | | |
| |     | | | | |
| | RED TIMINGS | | | | |
| |     | | | | |
| | GREEN TIMINGS | | | | |
| |     | | | | |

Drawing Notes

not scale from this drawing, all dimensions to be verified on site. It will be the responsibility of the contractor to ensure that all dimensions are correct.

It will be the responsibility of the contractor to ensure that all traffic management shall be in accordance with the Traffic Signs Manual chapter 8 2009, Safety at Street works 2013, Traffic Signs Regulations and General Directions 2016 and all current / relevant Health and

legislation.

Signage placement will be subject to available safe working areas and all signage will be secured / ballasted with straps or bags.

minimum lateral safety zone of 0.5M will be maintained at

minimum running lane of 3.0m will be maintained for

minimum running lane of 3.0m will be maintained for vehicles.

safe segregated working area will be provided and maintained at all times.

minimum size of temporary signage will be 750mm.